



iSECUREtrac ***House Arrest or Curfew Management***



Unsurpassed Flexibility

The iSt House Arrest system verifies a client's presence in a building, half-way house, residence, work release facility, etc. according to a customized schedule. Over the course of supervision, client surveillance needs may change. iSECUREtrac affords agencies the flexibility to shift from house arrest to GPS and back again, with the same unit and with the flip of a switch. By varying the intensity of electronic surveillance, for example, agencies can apply both incentives and disincentives in response to client behavior.

iSECUREtrac also provides landline and cellular communication options for its house arrest system because not every household or client has access to a landline phone.

User-friendly Software

Built for easy access and usability, iSECUREtrac software is securely accessed 24/7 from most any Internet-ready device, anywhere in the world. In addition to current client location, movement and status, historical data can be leveraged to assist law enforcement in solving criminal investigations.

Supplemental Services

As a complement to agency resources, iSECUREtrac provides a complete array of supplemental services including monitoring center intervention with direct offender contact to reduce agent work load and ensure program objectives are met.





iSt House Arrest System Features, Benefits and Specifications

<p style="text-align: center;">PTU</p> 	<p>Options: iSt Active and Passive GPS systems have ability to work in house arrest mode</p> <p>Tracking intervals: Continuous RF monitoring</p> <p>Tamper evidence: Light sensors automatically record and send violation alerts</p> <p>Communication coverage: Options include largest U.S. cellular carrier as well as traditional landline</p> <p>Reporting frequency: Normal reporting once per day; immediate notification of any curfew or compliance violations</p> <p>Durability: Made of high density ABS plastic to withstand extreme abrasion, chemical, corrosion, impact and water resistance</p> <p>Dimensions: 6" X 3.25" X 1.75"</p> <p>Weight: 13.2 ounces</p> <p>Battery: 30 hours continuous monitoring without power in passive mode</p>
<p style="text-align: center;">Transmitter Cuff</p> 	<p>Tamper evidence: Battery removal sensor in housing; optical and conductive strap for continuous tamper sensor</p> <p>Durability: Hypoallergenic, high impact and durable synthetic materials; water proof</p> <p>Dimensions: 2.5" X 1.75" X 0.9"</p> <p>Weight: 2.6 ounces</p> <p>Range: Average 130 – 150 feet</p>
<p style="text-align: center;">Charging Base</p> 	<p>Tamper evidence: Power sensor</p> <p>Durability: Made of high density ABS plastic</p> <p>Client feedback: Power and charge indicators</p> <p>Phone connectors: 2 standard connectors (type RJ-11)</p> <p>Dimensions: 8.75" X 6" X 3.75"</p> <p>Weight: Less than 2 pounds</p>

For more information on iSECUREtrac systems, software and services contact your iSECUREtrac representative at 866-537-0022 or visit www.isecuretrac.com